



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁶:

H04Q 7/38

A1

(11) International Publication Number:

WO 99/03295

(43) International Publication Date:

21 January 1999 (21.01.99)

(21) International Application Number: PCT/US98/13902

(22) International Filing Date: 7 July 1998 (07.07.98)

(30) Priority Data:

08/890,609

9 July 1997 (09.07.97)

US

(71) Applicant: ERICSSON INC. [US/US]; 7001 Development Drive, P.O. Box 13969, Research Triangle Park, NC 27709 (US).

(72) Inventors: ANDERSON, Keith, W.; 132 Wicklow Lane, Durham, NC 27713 (US). TOOT, Carl, B., Jr.; 4320 South Mountain Drive, Raleigh, NC 27603 (US).

(74) Agents: MOORE, Stanley, R. et al.; Jenkins & Gilchrist, P.C., Suite 3200, 1445 Ross Avenue, Dallas, TX 75202 (US).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).


Published

*With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*

(54) Title: INTEGRATION OF MOBILE STATION CHANNEL MEASUREMENT WITH PAGING CHANNEL DISPLACEMENT OPERATION IN WIRELESS COMMUNICATIONS SYSTEM

(57) Abstract

In connection with paging displacement operation, a mobile station delays entry into sleep mode in order to read a specified number of subsequent alternate (i.e., every other) additional paging channel slots to receive a paging message. During the paging channel slots located between those designated for reading paging displacement related paging messages, the mobile station makes more efficient use of limited battery supplied energy resources by making any requisite signal strength measurements.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

-1-

INTEGRATION OF MOBILE STATION CHANNEL MEASUREMENT
WITH PAGING CHANNEL DISPLACEMENT OPERATION
IN WIRELESS COMMUNICATIONS SYSTEM

5 BACKGROUND OF THE INVENTION

Technical Field of the Invention

The present invention relates to a wireless communications system and, in particular, to reducing mobile station power consumption in connection with paging and mobile station channel measurement operations.

Description of Related Art

It is well known that mobile stations (telephones) in wireless communications systems consume large amounts of power while operating in a talk mode. Consumption of power at a significant, albeit reduced, rate continues when the mobile station operates in a stand-by (i.e., idle) mode awaiting receipt or origination of a telephone call. For currently available portable, battery powered mobile stations, the on-board battery typically has a working lifetime of approximately eight hours in the stand-by mode and two hours in the talk mode. After such time expires, the battery must be recharged or replaced in order for the mobile station to continue to provide communications service.

Many methods and apparatus have been proposed to reduce power consumption in mobile stations and thus extend battery life between charges or replacement. A functional characteristic shared in common by many of these methods and apparatus is controlling mobile station operation by denying or reducing the supply of power to certain electronic components of the mobile station such as the transceiver, display or processor in order to reduce drain on the battery and extend useful battery life. This is commonly referred to as "sleep mode" operation. In order to obtain the maximum power

-2-

conservation benefit from sleep mode operation, it is important to maximize the amount of time the supply of power is denied or reduced. Efficient mobile station operation, however, depends on mobile station monitoring of control and command signals transmitted from the serving wireless communications system as well as making downlink signal strength measurements. These monitoring and measurement functions require the mobile station to be adequately powered to enable transceiver and processor operation. Accordingly, a balance must be struck between power conservation (sleep mode) operation and power consumption operation. Given the availability of sleep mode functionality, a need exists for a method and apparatus by which the time spent in sleep mode can be maximized without adversely affecting the ability of the mobile station to be sufficiently operational to carry out any required monitoring and measurement functions.

Reference is now made to FIGURE 1 wherein there is shown the structure of a hyperframe 10 for the forward (i.e., downlink) digital control channel (F-DCCH) as specified by the TIA/EIA Interim Standard IS-136 air interface. The hyperframe 10 is composed of two superframes 12. A first one these superframes 12(1) is commonly referred to as the "primary" superframe. A second one these superframes 12(2) is commonly referred to as the "secondary" superframe. Each superframe 12 is composed of a number of logical channels. A first one of these logical channels is a broadcast control channel (BCCH) commonly referred to as the fast broadcast control channel (F-BCCH) 14. This logical channel is used to broadcast control channel structure parameters and parameters that are essential for accessing the system. A next one of these logical channels is a broadcast control channel commonly referred to as the extended broadcast control channel (E-BCCH) 16. This logical channel carries broadcast information to mobile stations that is less time critical than the F-DCCH information.

-3-

Another one of these logical channels is a broadcast control channel commonly referred to as the short message service (SMS) broadcast control channel (S-BCCH) 18. This logical channel is used to broadcast short message service messages to mobile stations. Yet another one of these logical channels is commonly referred to as the SMS point-to-point, paging and access response channel (SPACH) 20. This logical channel is used to broadcast information to specific mobile stations regarding SMS messages, paging messages, and to provide an access response channel. Another defined logical channel (RES) 22 is reserved at this point in time for a future but not yet specified use.

The SMS point-to-point, paging and access response channel 20 is divided into three logical sub-channels. A first one of these sub-channels is the paging channel (PCH) 24 that is dedicated to delivering pages and orders. A next one of these sub-channels is the access response channel (ARCH) 26 that is used to convey assignments to another communications resource or other responses to a mobile station access attempt. Another one of these sub-channels is the SMS channel (SMSCH) 28 that is used to deliver short message service messages to a specific mobile station.

One superframe 12 includes thirty-two slots 30 for use by the broadcast control channels (BCCH) 14, 16 and 18, the reserved channel (RES) 22, and the SMS point-to-point, paging and access response channel (SPACH) 20. Of these thirty-two available slots 30, when full rate operation is specified, between one and twenty-eight slots are made available to the SMS point-to-point, paging and access response channel 20 for use by the paging channels (PCH) 24, access response channels (ARCH) 26 and the SMS channels (SMSCH) 28. Any of the slots 30 used for paging channels 22 in the primary superframe 12(1) are repeated for use in the secondary superframe 12(2). The other SMS point-to-point, paging and access response channel 20 related information, such as with respect to the access

-4-

response channel 26 and the SMS channel 28, may be different from one superframe 12 to a next superframe.

Each mobile station is assigned a particular one of the slots 30 in the SMS point-to-point, paging and access response channel 20 as its paging channel (PCH) 24. A mobile station camped on to the forward digital control channel the reads its assigned paging channel 24 to determine whether a message has been broadcast addressed to its mobile station identification (MSID). If there is no such message detected, the mobile station further reads a page continuation (PCON) bit carried in the slot 30 for its assigned paging channel 24. If the page continuation bit is clear (PCON=0), the mobile station enters sleep mode until the next occurrence of its assigned paging channel 24 on to the forward digital control channel (not shown). If, on the other hand, the page continuation bit is set (PCON=1), a page displacement functionality is activated and the mobile station responds by delaying entry into sleep mode in order to read additional slots 30 in the SMS point-to-point, paging and access response channel 20. The number of slots 30 which are then read is specified by a paging channel displacement parameter (PCH_DISPLACEMENT) sent over the forward digital control channel.

When full rate operation is specified, the mobile station reads every other slot 30 in the SMS point-to-point, paging and access response channel 20 following its assigned paging channel 24 slot until the number of slots read equals the number specified in the paging channel displacement parameter or it receives a paging message addressed to its mobile station identification. In the situation where the mobile station has read the last available slot 30 in the SMS point-to-point, paging and access response channel 20 of the primary superframe 12(1), and the paging displacement parameter specifies that additional slots be read, the mobile station starts again reading with the second slot in the SMS point-to-

-5-

point, paging and access response channel of the next primary superframe. In the situation where the mobile station has read the next-to-last available slot 30 in the SMS point-to-point, paging and access response channel 20 of the primary superframe 12(1), and the paging displacement parameter specifies that additional slots be read, the mobile station starts again reading with the first slot in the SMS point-to-point, paging and access response channel of the next primary superframe. A

10 example of paging displacement operation is shown in FIGURE 2. In this example of full rate operation for the forward digital control channel, the SMS point-to-point, paging and access response channel 20 is assigned six slots 30(1)-30(6). Assume that a given mobile station is assigned a paging channel 24 that occurs in slot 30(1) of

15 the first illustrated primary superframe 12(1). The mobile station wakes up and reads this paging channel 24 (as indicated by "X") to determine whether a message has been broadcast addressed to its mobile station identification (MSID). If there is no such message detected, the mobile station further reads a page continuation (PCON) bit. If the page continuation bit is clear (PCON=0), the mobile station enters sleep mode until

20 the next occurrence (not shown) of its assigned paging channel 24 on the forward digital control channel. If, on the other hand, the page continuation bit is set (PCON=1), the mobile station reads every other slot (30(3), 30(5)) in the SMS point-to-point, paging and access response channel 20 following the slot 30(1) for its assigned

25 paging channel 24 (as indicated by "Y") until the number of slots read equals the number specified in the paging channel displacement parameter (PCH_DISPLACEMENT=4 in this example) or it receives a paging message addressed to its mobile station identification. When the mobile station

30 reads the next-to-last available slot 30(5) in the SMS point-to-point, paging and access response channel 20 of the first illustrated primary superframe 12(1), and the

35

-6-

5 paging displacement parameter specifies that additional slots be read, the mobile station starts again reading with the first slot 30(1) in the SMS point-to-point, paging and access response channel of the second illustrated (i.e., the next following) primary superframe.

10 Not only must a mobile station wake up to read its assigned paging channel, it must also wake up periodically to make signal strength measurements. Although these measurements are not required to be performed at any particular place in the superframe, they are typically performed immediately before or after the paging data. These measurements are made on the control channels of cells in the wireless communications system which neighbor the cell currently serving the mobile station. The signal strength measurements are then processed by the mobile station for the purpose of making server selection determinations.

20 Paging displacement provides a mechanism by which the wireless communications system can force mobile stations to postpone entry into sleep mode and make additional reads on the forward digital control channel for the purpose of finding pages. Postponing entry into sleep mode and requiring transceiver and processor operation to make additional control channel reads places additional demands on the stored energy resources of the mobile station battery. Even the reading of a few extra slots can significantly shorten battery life. The additional periodic requirement to make signal strength measurements further serves as a drain on the limited energy resources of the battery. A method and apparatus are needed to maximize the time spent in sleep mode so as to conserve battery resources while simultaneously facilitating mobile station operation to make requisite signal strength measurements and support the paging channel displacement functionality.

35

-7-

SUMMARY OF THE INVENTION

When paging displacement functionality is activated by a command sent during a paging channel slot assigned to a given mobile station, that mobile station responds by delaying entry into sleep mode. This delay allows the given mobile station to read a specified number of subsequent additional paging channel slots for a paging message. In particular, the mobile station reads every other paging channel slot following the assigned paging channel slot until the specified number of slots have been read. In support of more efficient utilization mobile station battery supplied energy resources, the given mobile station further makes requisite signal strength measurements during the paging channel slots positioned between the every other paging channel slots specified to be read by the mobile station in connection with the activated paging displacement functionality.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the method and apparatus of the present invention may be obtained by reference to the following Detailed Description when taken in conjunction with the accompanying Drawings wherein:

FIGURE 1, previously described, illustrates the structure of a hyperframe for the forward (i.e., downlink) digital control channel (F-DCCH) as specified by the TIA/EIA Interim Standard IS-136 air interface;

FIGURE 2, previously described in part, illustrates an example of paging displacement operation along with integrated signal strength measurement;

FIGURE 3 is a flow diagram illustrating mobile station operation in accordance with the present invention to integrate paging displacement operation with signal strength measurement; and

FIGURE 4 is a simplified block diagram of a mobile station.

-8-

DETAILED DESCRIPTION OF EMBODIMENTS

Reference is now made to FIGURE 3 wherein there is shown a flow diagram illustrating mobile station operation in accordance with the present invention to integrate paging displacement operation with signal strength measurement. The process illustrated in the flow diagram concerns mobile station decision making in the awake mode with respect to what to do with and during slots 30 (FIGURE 2) of the repeating hyperframe. In decision step 100, a determination is made as to whether the current slot is designated as the paging channel for that mobile station. If yes, the mobile station reads the slot in step 102 for paging channel related data. The read data may comprise a paging notification, or include an indication from the state of the included PCON bit (i.e., PCON=1) that paging continuation has been activated. A determination is then made in decision step 104 as to whether PCON=1. If not, the mobile station enters sleep mode in step 106, awakening again when necessary (such as for reading the paging channel or for making measurements). If yes, the mobile station remains awake in step 108, and then the process returns in step 110 to decide what to do with the next slot.

If the slot is not the paging channel (step 100), a determination is made in step 112 as to whether the current slot is designated for paging channel displacement use by that mobile station. If yes, the mobile station reads the slot in step 114 for a paging notification. A determination is then made in decision step 116 as to whether a paging notification was read. If yes, the mobile station enters sleep mode in step 118. If not, the mobile station then determines in decision step 120 whether paging continuation has terminated. If yes, the mobile station enters sleep mode in step 118. If not, the mobile station remains awake in step 122, and then the process returns in step 124 to decide what to do with the next slot.

-9-

If the slot is not for paging displacement (step 112), a determination is made in step 126 as to whether the mobile station has signal strength measurements which need to be made. If yes, the mobile station makes signal strength measurements in step 128, remains awake in step 130, and then the process returns in step 132 to decide what to do with the next slot. If no, the mobile station then determines in decision step 134 whether paging continuation has terminated. If yes, the mobile station enters sleep mode in step 136. If not, the mobile station remains awake in step 138, and then the process returns in step 140 to decide what to do with the next slot.

The process of FIGURE 3 may be better understood in the context of a specific example. Accordingly, reference is again made to FIGURE 2 wherein an example (discussed above) of paging displacement operation is shown. In this example of full rate operation for the forward digital control channel, the SMS point-to-point, paging and access response channel 20 is assigned six slots 30(1)-30(6). Assume that a given mobile station is assigned a paging channel 24 that occurs in slot 30(1) of the first illustrated primary superframe 12(1). The mobile station wakes up and reads this paging channel 24 (as indicated by "X") to determine whether a message has been broadcast addressed to its mobile station identification (MSID). If there is no such message detected, the mobile station further reads a page continuation (PCON) bit. If the page continuation bit is clear (PCON=0), the mobile station enters sleep mode until the next occurrence (not shown) of its assigned paging channel 24 on the forward digital control channel (not shown) or until such time as necessary to access the control channel or make measurements. If, on the other hand, the page continuation bit is set (PCON=1), the mobile station reads every other slot (30(3), 30(5)) in the SMS point-to-point, paging and access response channel 20 following the slot 30(1) for its assigned paging channel 24 (as indicated by

-10-

"Y") until the number of slots read equals the number specified in the paging channel displacement parameter (PCH_DISPLACEMENT=4 in this example) or it receives a paging message addressed to its mobile station identification. When the mobile station reads the next-to-last available slot 30(5) in the SMS point-to-point, paging and access response channel 20 of the first illustrated primary superframe 12(1), and the paging displacement parameter specifies that additional slots be read, the mobile station starts again reading with the first slot 30(1) in the SMS point-to-point, paging and access response channel of the second illustrated (i.e., the next following) primary superframe. Furthermore, if the mobile station has signal strength measurements to perform, these measurements are made, while the mobile station remains awake, during the slots 30 (as indicated by "M") in the SMS point-to-point, paging and access response channel 20 following the slot 30(1) located between those slots utilized for paging channel displacement (as indicated by "Y").

By making measurements during these "M" slots 30, a more efficient use of limited mobile station battery resources is made. The mobile station now need not wake up at a later time (i.e., following paging activity or before next paging activity) to make the measurements. Furthermore, the mobile station need not waste resources remaining awake without performing any functions during the previously unused slots while waiting to complete the paging displacement operation.

Reference is now made to FIGURE 4 wherein there is shown a simplified block diagram of a mobile station 210 operating in accordance with the present invention. The mobile station 210 includes a processor 212 connected to a transceiver 214. An antenna 216 is connected to the transceiver 214 for transmitting and receiving communications (both voice and data) over a wireless communications system. Power for the mobile station 210

-11-

is supplied by a renewable or replaceable power source 218 typically comprising a battery. There are other components 220 included in the mobile station 210 (like a handset, keypad, etc.) and not shown in FIGURE 1 whose nature, operation and interconnection with the illustrated components are known to those skilled in the art.

The mobile station 210 functions in accordance with four primary modes of operation. The first mode comprises a "talk" mode wherein a subscriber uses the mobile station 210 to communicate over the wireless communications system. As is well known to those skilled in the art, because nearly all of the components of the mobile station 210 are operating during the talk mode, this mode of operation consumes an enormous amount of power output from the power source 218. Such power consumption will quickly drain the power source 218.

The second mode comprises a "stand-by" (or idle) mode wherein the mobile station 210 awaits use by the subscriber in originating or receiving a telephone call or messages. While in the stand-by mode, some of the components of the mobile station 210 continue to operate and thus continue to require and consume power (perhaps at a reduced rate) supplied by the power source 218. Other components, though, are unused and not operating and thus do not significantly consume power. Accordingly, overall power consumption occurs at a reduced rate in comparison to that experienced with the talk mode.

The third mode of operation comprises an "off" mode where the subscriber simply turns off the mobile station 210. In fact, placement of the mobile station 210 in the off-mode often involves using a switch to disconnect the power source 218 from many of the mobile station components. Accordingly, in the off mode little to no power is drained from the power source 218 by the mobile station 210 because few, if any, of the components of the mobile station continue to operate. Placement of the mobile station in the off mode provides the most effective

-12-

means for conserving power supplied by the power source 218.

5 The fourth mode of operation comprises a "sleep" mode that may be described as being relatively positioned, as far as operation is concerned, somewhere between the previously described stand-by and off modes of operation. In the sleep mode of operation, certain ones of, but not necessarily all of, the components of the mobile station 210 are temporarily shut off (denied power) in order to
10 conserve the drain of power from the power source 218. By denying power to such components, overall power consumption by the mobile station 210 occurs at a reduced rate in comparison to that experienced with the stand-by mode.

15 To facilitate this fourth mode of operation, the mobile station 210 further includes power control circuitry 222. In accordance with mobile station programming (like that illustrated in FIGURE 3) as executed by the processor 212, power control circuitry 222
20 regulates the supply of power to the mobile station 210 components. When operation in the sleep mode is specified by mobile station programming, the power control circuitry 222 denies power to certain components of the mobile station 210 (e.g., the transceiver 214). When necessary,
25 and again in accordance with mobile station programming, the mobile station 210 awakens back into the stand-by mode ready to receive and transmit telephone calls (by further entering into the talk mode), as well as to receive messages (such as pages) and make any needed signal
30 strength measurements.

35 Although a preferred embodiment of the method and apparatus of the present invention has been illustrated in the accompanying Drawings and described in the foregoing Detailed Description, it will be understood that the invention is not limited to the embodiment disclosed, but is capable of numerous rearrangements, modifications and substitutions without departing from the spirit of the

-13-

invention as set forth and defined by the following claims.

-14-

WHAT IS CLAIMED IS:

5 1. A method for integrating paging channel displacement operation and downlink signal strength measurement operation with respect to mobile station operation, comprising the steps of:

reading a certain number of every other paging channel designated slots of a forward control channel following an assigned paging channel slot for mobile station paging messages; and

10 making downlink signal strength measurements during paging channel designated slots located between the certain number of every other paging channel designated slots of the forward control channel.

15 2. The method as in claim 1 further including the step of entering into a sleep mode of operation following the reading of the every other paging channel designated slots.

20 3. The method as in claim 1 further including the step of entering into a sleep mode of operation following reading of a mobile station paging message.

25 4. The method as in claim 1 wherein the paging channel designated slots are located within a short message service (SMS) point-to-point, paging and access response channel (SPACH) of the forward control channel.

30 5. A mobile station, comprising:
a transceiver for reading a forward control channel for paging messages, and for making downlink signal strength measurements; and

35 a processor connected to the transceiver and operating to cause the transceiver to read a certain number of every other paging channel designated slots of the forward control channel following an assigned paging channel slot for mobile station paging messages, and

-15-

further make downlink signal strength measurements during paging channel designated slots located between the certain number of every other paging channel designed slots of the forward control channel.

5

6. The mobile station as in claim 5 further including means for denying power to the transceiver to cause entry into a sleep mode of operation following the reading of the every other paging channel designated slots.

10




7. The mobile station as in claim 5 further including means for denying power to the transceiver to cause entry into a sleep mode of operation following reading of a mobile station paging message.

15

8. The mobile station as in claim 5 wherein the paging channel designated slots are located within a short message service (SMS) point-to-point, paging and access response channel (SPACH) of the forward control channel.

20

THIS PAGE BLANK (USPTO)



THIS PAGE BLANK (USPTO)

2/2




FIG. 3

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/13902

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H04Q7/38

According to International Patent Classification(IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y A	WO 95 12931 A (ERICSSON TELEFON AB L M ;SAMMARCO ANTHONY J (US)) 11 May 1995 see page 18, line 24 - page 19, line 18 see page 28, line 1 - page 43, line 16 ----	1,2,4,5, 8 3,6,7
Y A	WO 95 12932 A (ERICSSON TELEFON AB L M ;RAITH ALEX K (US)) 11 May 1995 see page 10, line 15 - page 19, line 2 -----	1,2,4,5, 8 3,7

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

Date of the actual completion of the international search

22 October 1998

Date of mailing of the international search report

11/11/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Maalismaa, J

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/US 98/13902

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9512931 A	11-05-1995	US 5603081 A	11-02-1997
		US 5604744 A	18-02-1997
		AU 681730 B	04-09-1997
		AU 1048095 A	23-05-1995
		AU 680071 B	17-07-1997
		AU 1048395 A	23-05-1995
		AU 691850 B	28-05-1998
		AU 1087495 A	23-05-1995
		AU 685885 B	29-01-1998
		AU 1087695 A	23-05-1995
		AU 695892 B	27-08-1998
		AU 2079997 A	24-07-1997
		AU 2358897 A	14-08-1997
		AU 690924 B	07-05-1998
		AU 7757094 A	18-05-1995
		AU 8131394 A	23-05-1995
		AU 681721 B	04-09-1997
		AU 8131494 A	23-05-1995
		BR 9404316 A	04-07-1995
		BR 9405702 A	28-11-1995
		BR 9405703 A	28-11-1995
		BR 9405704 A	28-11-1995
		BR 9405705 A	28-11-1995
		BR 9405743 A	05-12-1995
		BR 9405927 A	05-12-1995
		CA 2134695 A	02-05-1995
		CA 2152942 A	11-05-1995
		CA 2152943 A	11-05-1995
		CA 2152944 A	11-05-1995
		CA 2152945 A	11-05-1995
		CA 2152946 A	11-05-1995
		CA 2152947 A	11-05-1995
		CN 1112345 A	22-11-1995
		CN 1117329 A	21-02-1996
		CN 1116888 A	14-02-1996
		CN 1117330 A	21-02-1996
		CN 1117331 A	21-02-1996
		CN 1124074 A	05-06-1996
		CN 1117332 A	21-02-1996
		EP 0652680 A	10-05-1995

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/13902

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9512931 A		EP 0682829 A	22-11-1995
		EP 0679304 A	02-11-1995
		EP 0677222 A	18-10-1995
		EP 0681766 A	15-11-1995
		EP 0677223 A	18-10-1995
		EP 0677224 A	18-10-1995
		FI 953262 A	30-08-1995
		FI 953263 A	30-06-1995
		FI 953264 A	30-06-1995
		FI 953265 A	30-06-1995
WO 9512932 A	11-05-1995	US 5603081 A	11-02-1997
		US 5539748 A	23-07-1996
		AU 681730 B	04-09-1997
		AU 1048095 A	23-05-1995
		AU 680071 B	17-07-1997
		AU 1048395 A	23-05-1995
		AU 691850 B	28-05-1998
		AU 1087495 A	23-05-1995
		AU 685885 B	29-01-1998
		AU 1087695 A	23-05-1995
		AU 695892 B	27-08-1998
		AU 2079997 A	24-07-1997
		AU 2358897 A	14-08-1997
		AU 690924 B	07-05-1998
		AU 7757094 A	18-05-1995
		AU 8131394 A	23-05-1995
		AU 681721 B	04-09-1997
		AU 8131494 A	23-05-1995
		BR 9404316 A	04-07-1995
		BR 9405702 A	28-11-1995
		BR 9405703 A	28-11-1995
		BR 9405704 A	28-11-1995
		BR 9405705 A	28-11-1995
		BR 9405743 A	05-12-1995
		BR 9405927 A	05-12-1995
		CA 2134695 A	02-05-1995
		CA 2152942 A	11-05-1995
		CA 2152943 A	11-05-1995
		CA 2152944 A	11-05-1995

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/US 98/13902

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9512932 A		CA 2152945 A	11-05-1995
		CA 2152946 A	11-05-1995
		CA 2152947 A	11-05-1995
		CN 1112345 A	22-11-1995
		CN 1117329 A	21-02-1996
		CN 1116888 A	14-02-1996
		CN 1117330 A	21-02-1996
		CN 1117331 A	21-02-1996
		CN 1124074 A	05-06-1996
		CN 1117332 A	21-02-1996
		EP 0652680 A	10-05-1995
		EP 0682829 A	22-11-1995
		EP 0679304 A	02-11-1995
		EP 0677222 A	18-10-1995
		EP 0681766 A	15-11-1995
		EP 0677223 A	18-10-1995
		EP 0677224 A	18-10-1995
		FI 953262 A	30-08-1995
		FI 953263 A	30-06-1995
		FI 953264 A	30-06-1995
		FI 953265 A	30-06-1995

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)